



STYLE 810

PTFE FLANGE SEAL AND GASKET MATERIAL



RANGE OF APPLICATIONS

Steam, water, condensate, chemicals, gases, oils, solvents etc. (exception: molten alkali-metals)

EQUIPMENT

Flanges, lids, gear units, mixers, agitators, reactor vessels, covers, pumps, etc.

INDUSTRIES

Can be used by all industries including marine

THE NON-ASBESTOS ALTERNATIVE

THE UNIVERSALLY APPLICABLE SELF-ADHESIVE SEAL FOR FLANGES, COVERS AND LIDS

- Temp. - 330° F to + 530° F
(- 200° C to + 260° C)
- pH-Range 0-14
- Pressure 3000 PSI (200 bar)
- Staining no

NON-ASBESTOS

The industry is increasingly determined to replace asbestos packings by different alternative products.

DEPAC STYLE 810 is such modern non-asbestos replacement which is applicable to a wide variety of equipment.

CHEMICAL RESISTANCE

DEPAC STYLE 810 is made of 100% PTFE. It is very special and new that this PTFE material cannot be extruded in spite of its softness and pliancy. Unlike conventional flat gasket materials **TYPE 810** fills all voids and adjusts readily and completely to uneven flange surfaces.

GASKETING MADE TO MEASURE

The self-adhesive surface decreases maintenance work to an absolute minimum. Splippage during installation work, especially during „on the spot jobs“, will be eliminated. The self-adhesive surface attached to the packing only needs to be pulled off whereas the packing is squeezed onto the flange or surface. Carefully overlap the ends and tighten the flange bolts or lid parts — finished. There is no simpler method!

UNIVERSAL USAGE

DEPAC STYLE 810 is non-reactive throughout the entire pH-range of 0-14 with the only exception of molten alkali-metals. Because of this and its outstanding compression strength **DEPAC STYLE 810** is not only a fast and highly effective sealant for flanges and lids but also for all kinds of different equipment for the entire industry.



STYLE 810

PTFE FLANGE SEAL AND GASKET MATERIAL

DEPAC STYLE 810 was developed to provide an instant packing simplifying considerably the maintenance work on flanges, covers, lids etc.

DEPAC STYLE 810 is an efficient, easy to use, easy to carry and easy to apply sealant for a wide variety of applications. The material is soft and pliable, it never hardens, never adheres and is completely inert. It is clean and economical.

DEPAC STYLE 810 is an instant gasket eliminating the costly cutting of gaskets from gasket sheets in order to fit the many different flange configurations to be sealed. There will be no more need for large inventories of different gaskets as any gasket size can be formed using this packing following simple installation instructions.

APPROXIMATE DATA				
Reorder No.	With x Thickness		Length	
	mm	inch	m	ft
81003	3 x 1.5	1/8 x 1/16	10 25	35 80
81005	5 x 2	3/16 x 3/32	10 25	35 80
81007	7 x 2.5	1/4 x 3/32	10 25	35 80
81010	10 x 3	3/8 x 1/8	10 25 50	35 80 160
81014	14 x 5	9/16 x 3/16	10 25 50	35 80 160
81017	17 x 6	11/16 x 1/4	5 10 25	16 35 80
81020	20 x 7	13/16 x 1/4	5 10 25	16 35 80

Other sizes and length on request.

POSSIBILITY FOR STANDARDIZATION

Recommended width

Up to pipesize	2"	with	1/8"
	8"		3/16"
	25"		1/4"
	60"		3/8"
above	60"		9/16 11/16 13/16"

DEPAC AG
Neugrüt 994
FL-9496 Balzers/Liechtenstein
Telephone 075-42844
Telefax 075-42836

DEPAC GMBH
Ackerstraße 36
D-4900 Herford/Germany
Telephone 05221/57766
Telex 934926
Telefax 05221/57788

DEPAC SEALING LTD.
Grant Thornton
Bold Street Chambers
31 Bold Street
GB-Warrington WA1 1HL/England
Telephone 0925-31333
Telefax 0925-413899

DEPAC INC.
The Company Corporation 9018442
725 Market Street
USA-Wilmington/Delaware 19801
Telephone 302-575 0440
Telefax 302-575 1346

**KUNGÄLV SEAL-PACK AB
(DEPAC SWEDEN)**
Backa Bergögata 10
S-42246 Hisings Backa/Sweden
Telephone 031-581220
Telefax 031-526115

DEPAC GES.M.B.H.
Bahnhofstraße 26
A-6710 Nenzing/Austria
Telephone 05525-3401
Telefax 05525-3358

Erhältlich durch:
Available through: