



Standardutførelse:

Belg: AISI 321
 Kraver: AISI 316-Ti. 3,0mm
 Flenser: RSt. 37-2

Designtrykk: 16 [barg]

PN 16

DN	TYPE	Bevegelse		Ln	Stivhet		Flenser borret etter PN16					Di	Do	Belg-areal	Vekt
		+/-AX	+/-LA		AX	LA	D	b	k	N	d2				
		[mm]	[mm]												
40	0040-016-0	16	8	110	143	85	150	16	110	4	18	41,0	59,0	1963	3,8
50	0050-025-0	25	16	150	154	48	165	18	125	4	18	50,5	68,0	2757	5,2
65	0065-025-0	25	13	150	250	172	185	18	145	4	18	66,0	86,0	4766	6,4
80	0080-025-0	25	10	150	322	426	200	20	160	8	18	77,0	100,0	6362	6,6
100	0100-025-0	25	7	150	285	447	220	20	180	8	18	103,0	127,0	10825	8,8
125	0125-025-0	25	6	150	263	896	250	22	210	8	18	128,0	155,0	16286	12,0
150	0150-025-0	25	5	150	243	1263	285	22	240	8	22	153,0	186,6	22912	15,4
200	0200-040-0	40	8	155	254	1072	340	26	295	12	22	203,0	236,0	37841	21,4
250	0250-040-0	40	6	165	393	2746	405	32	355	12	26	257,0	293,0	59396	36,0
300	0300-035-0	35	4	165	549	5540	460	32	410	12	26	308,0	346,0	83982	43,6