



Designtrykk: 16 [barg]

DN	TYPE	Bevegelse		Ln	Stivhet		Flenser borret etter PN 10					Di	Do	Belg-areal	NRF nr
		+/-AX	+/-LA		AX	LA	D	b	k	N	d2				
		[mm]	[mm]	[mm]	[N/mm]	[N/mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm ²]	
40	41.156.10	19	16	148	109	39	150	18	110	4	18	38,9	54,1	1698	8541531
50	41.207.10	18	9	145	119	110	165	20	125	4	18	50,9	68,1	2781	8541532
65	41.208.10	20	8	145	115	171	185	20	145	8	18	66,9	85,1	4536	8541533
80	41.209.10	21	5	155	125	440	200	20	160	8	18	87,9	112,1	7854	8541534
100	41.210.10	29	5	160	159	775	220	22	180	8	18	112,5	142,3	12748	8541535
125	41.211.10	19	2	150	210	2805	250	22	210	8	18	138,4	169,0	18554	8541536
150	41.212.10	24	3	170	348	4887	285	24	240	8	22	166,1	203,5	26822	8541537
200	41.214.10	32	3	180	410	8186	340	26	295	12	22	214,9	259,1	44115	8541538