



Designtrykk: 16 [barg]

PN 16

DN	TYPE	Bevegelse		Ln	Stivhet		Flenser borret etter PN 10					Di	Do	Belg-areal	Vekt
		+/-AX	+/-LA		AX	LA	D	b	k	N	d2				
		[mm]	[mm]												
40	0040-016-0	16	8	110	143	85	150	16	110	4	18	41,0	59,0	1963	3,8
40	0040-027-0	27	27	190	143	22	150	16	110	4	18	41,0	59,0	1963	4,0
50	0050-022-0	22	12	115	119	67	165	18	125	4	18	50,5	68,0	2757	5,2
50	0050-032-0	32	32	195	136	23	165	18	125	4	18	50,5	68,0	2757	5,6
65	0065-026-0	26	11	115	97	92	185	18	145	4	18	66,0	86,0	4766	6,4
65	0065-038-0	38	30	195	114	32	185	18	145	4	18	66,0	86,0	4766	6,8
80	0080-025-0	25	10	135	211	192	200	20	160	8	18	77,0	100,0	6362	6,6
80	0080-048-0	48	38	230	176	45	200	20	160	8	18	77,0	100,0	6362	7,4
100	0100-023-0	23	6	110	200	518	220	20	180	8	18	103,0	127,0	10825	8,8
100	0100-048-0	48	26	205	109	65	220	20	180	8	18	103,0	127,0	10825	9,2
125	0125-027-0	27	6	120	202	650	250	22	210	8	18	128,0	155,0	16286	12,0
125	0125-060-0	60	30	240	142	92	250	22	210	8	18	128,0	155,0	16286	13,6
150	0150-037-0	37	9	145	215	566	285	22	240	8	22	153,0	186,6	22912	15,4
150	0150-069-0	69	30	240	116	101	285	22	240	8	22	153,0	186,6	22912	16,4
200	0200-040-0	40	8	155	254	1072	340	26	295	12	22	203,0	236,0	37841	21,4
200	0200-083-0	83	30	260	169	220	340	26	295	12	22	203,0	236,0	37841	25,0
250	0250-040-0	40	6	165	393	2746	405	32	355	12	26	257,0	293,0	59396	36,0
250	0250-075-0	75	25	305	236	367	405	32	355	12	26	257,0	293,0	59396	41,8
300	0300-035-0	35	4	165	549	5540	460	32	410	12	26	308,0	346,0	83982	43,6
300	0300-100-0	100	33	360	256	390	460	32	410	12	26	308,0	346,0	83982	54,6